



ÁREA: Catálise ambiental, fotocatalise e eletrocatalise

Evaluation of BiVO_4 as a photocatalyst in the photocatalysis process of effluent generated in biodiesel production

Maria J. L. Barbosa^{1*}, Maria E. A. Vieira¹, Alessandra R. de Oliveira¹, Keurison F. Magalhães¹, Suely S. L. de Castro¹

¹ Laboratório de Eletroquímica e Química Analítica, Universidade do Estado do Rio Grande do Norte (UERN), Mossoró-RN, 59.610-210, Brasil

*E-mail: limabarbosa@alu.uern.br

Resumo-Abstract

In recent years, Brazil has excelled in the production of biodiesel, diversifying its energy matrix. Law No. 11.097/2005 establishes a gradual increase in the percentage of biodiesel in diesel, from 2% to 12%[1]. Biodiesel is obtained by transesterifying triglycerides from vegetable oils or animal fats with methanol or ethanol, generating esters and glycerin. Purification involves washing, resulting in effluents that need to be treated and reused. With this, it is possible to reduce the amount of waste and minimize environmental impacts, making the process more sustainable and efficient[2]. To treat these effluents, advanced oxidative processes such as heterogeneous photocatalysis are highly effective, using solid catalysts activated by UV light to decompose organic and inorganic pollutants present. Bismuth vanadate (BiVO_4) stands out for its high photocatalytic efficiency, especially when activated by UV light, making it an effective and promising alternative for mitigating the negative impacts associated with environmental pollution. The aim of this study is to use heterogeneous photocatalysis with BiVO_4 and UV radiation to promote the efficient and sustainable degradation of contaminated effluents generated in biodiesel production, with a view to environmental protection. The photocatalyst was synthesized via the hydrothermal method using ammonium metavanadate and bismuth nitrate, after which the powder was calcined at 400°C. The biodiesel was obtained via methyl transesterification with sodium hydroxide (NaOH), and soybean oil heated to 60°C under stirring for 1 hour. After 24 hours, the glycerin was separated and the biodiesel washed until the residual water reached pH 7. The photolysis and photocatalysis experiments were conducted using an 80W mercury lamp in a jacketed reaction cell. The pH of the samples was kept neutral and the concentrations of BiVO_4 varied between 500 and 1000 ppm. Aliquots of 5 mL were taken throughout the experiment and centrifuged to determine pH, conductivity and temperature and UV-Vis in the 200 to 800 nm range, the analyses were carried out and quickly returned to the reaction medium. Representative samples from the initial and final times were preserved for Total Organic Carbon (TOC) analysis in order to gauge the efficiency of the degradation processes. The study compared the effectiveness of photocatalysis with BiVO_4 and photolysis in the treatment of biodiesel effluents. Photocatalysis with 500 ppm of BiVO_4 at neutral pH was the most efficient, with a degradation rate of 30%, while the sample with 1000 ppm presented similar results, the concentration of 500 ppm was chosen due to the smaller amount of catalyst used, and photolysis had inferior performance.

Keywords: Advanced oxidative processes, BiVO_4 , Environmental sustainability.

References

[1] Brazil. Law No. 11.097, of January 13, 2005. Introduces biodiesel into the Brazilian energy matrix and makes other provisions. Federal Official Gazette: section 1, Brasília, DF, p. 1, January 14, 2005.

[2] ANDREOZZI, R.; CAPRIO, V.; INSOLA, A.; MAROTTA, R. Advanced oxidation processes (AOP) for water purification and recovery. *Catalysis Today*, v. 53, n. 1, p. 51-59, 1999.

Acknowledgements

We would like to thank CNPq; UERN; the Laboratory of Electrochemistry and Analytical Chemistry (LEQA) at UERN; the Laboratory of Environmental Catalysis and Materials (LACAM) at UERN.